

CORDOVA BATH

IMPORTANT USERS INSTRUCTIONS

**PLEASE READ CAREFULLY AND RETAIN FOR FURTHER USE.
IMPROPER USE OR CARE CAN INVALIDATE THE WARRANTY.**

OPERATING INSTRUCTIONS

The CORDOVA bath features an inward opening glass door for easy access. The watertight door is held firmly in a locked position by means of a latch lock.

The bath must only be filled and emptied of water when the door is in the locked position. Two bath wastes are incorporated for faster drainage and safety should one fail. Door should always be left open when not in use to prevent wear out of the seal.

- 1) Close the two wastes and enter bath.
- 2) Shut door and pull on door to check it is locked.
- 3) Turn the taps on and fill the bath to desired depth.

BATH IS NOW WATERTIGHT AND READY FOR FILLING

- 4) After bathing open the two wastes to drain the water and remain seated whilst bath is draining.
- 5) When bath has drained pull door knob upwards to release and open door.
- 6) Exit bath. Leave the door unlocked to ensure seal is not permanently compressed.

FILL BATH ONLY WHEN OCCUPIED AND DOOR SHUT

** NEVER ATTEMPT TO OPEN DOOR WHEN BATH IS FILLED WITH WATER **

** DO NOT LEAN ON DOOR OR USE FOR SUPPORT **

** LEAVE DOOR OPEN WHEN NOT IN USE **

CARE AND MAINTENANCE

The CORDOVA Bath is manufactured to a very high standard in G.R.P. (Reinforced Plastic) to ensure its durability and appearance is maintained over many years of use. It has a robust, smooth and warm surface which is non-porous, resistant to dirt and bacteria and easy to clean and maintain.

This bath will give many years of service and continue to look good if cleaned correctly and treated with care.

CLEANING

1. As with standard baths, cleaning will vary subject to the scale residue dependent on the hard or soft water level. In soft water areas, wash down with warm water and detergent applied with a soft cloth or sponge. In hard water areas, non-abrasive or mild acid cleansers can be used. Clean regularly followed by wiping with a dry soft cloth.

Do not use any form of abrasive cleaners on bath tub, the painted seat back plate/crossbar, the dome seal housing and the hydraulic piston. Widely available proprietary plastic/enamel bath cleansers are ideal cleaning agents that offer the advantage of a polished shine without rubbing down.

For the extra sparkle, and to further preserve the surface, the Bath can be gently polished occasionally. Beeswax and Brasso (Brass Polish) are suitable for this purpose. Polishing the anti-slip base should be treated with caution so as not to diminish its effectiveness.

2. The latch lock can be lubricated occasionally. For convenience use 'Mr Sheen General Aerosol Polisher' as it has excellent lubrication properties.
3. The white silicone seal along bath door sides should be cleaned occasionally. Use detergent and warm water applied with a sponge or soft cloth. Apply gently and refrain from excessive rubbing.
4. Ideally all chrome or gold plated furniture should be wiped down dry after use. Clean with soapy water and buff with a dry soft cloth only. Note: Surfaces can easily be damaged with acid/abrasive cleaners or with a rough cloth/sponge.

CAUTION

- **DO NOT LOCK THE DOOR WHEN BATH IS NOT IN USE AS THIS WILL WEAR OUT THE SEAL .**
- **KEEP THE WHITE SILICONE SEAL FREE OF ANY BUILD UP OF DEPOSITS. CLEAN GENTLY AND AVOID UNNECESSARY HANDLING.**
- **DO NOT APPLY ANY UNDUE FORCE TO THE BATH DOOR. HANDLE GENTLY.**



SNB Ltd 37 Warren Street London W1T 6AD
13
EN 14516: CLASS 2

Aug 2018